MAKABAGONG ADUANA, MATATAG NA EKONOMIYA



REQUEST FOR QUOTATION

The Bureau of Customs (BOC), through its Administration Office (AO), will undertake a Small Value Procurement for "Supply and Delivery of PIAD Equipment for Production and Documentation of OCOM Activities & Other BOC-Related Events" in accordance with the Revised Implementing Rules and Regulations of Republic Act No. 9184. The details of the project are as follows:

Name of Project: Supply and Delivery of PIAD Equipment for

Production and Documentation of OCOM Activities

& Other BOC-Related Events

Location: General Services Division, OCOM Building, Gate 3,

South Harbor, Port Area, Manila

Approved Budget for the Contract:

Two Hundred Ninety-Seven Thousand Five

Hundred Pesos

(PHP221,313.06) - inclusive of tax

Specifications:

Unit	Description/Specifications	Qty
pcs	 H5 Handy Recorder Microphone Number of Tracks 2 Max Sample Rate/Resolution 96 kHz / 24-Bit Microphone Built-In Cardioid Stereo Pair, X/Y Configuration Built-In Speaker Yes, 400 mW Mono Display LCD (Backlit) Memory Card Support SD, SDHC Audio File Formats BWF, MP3, WAV Sample Rates WAV: 44.1 / 48 / 96 kHz (Stereo) MP3: 44.1 kHz Bit Depth 16/24-Bit Bit Rates 48 to 320 kb/s 48 to 320 kb/s Timecode No Analog I/O 1 x 1/8" / 3.5 mm TRS Line/Mic Input 2 x Combo XLR / 1/4" TRS Input 1 x 1/8" / 3.5 mm TRS Line Output 1 x 1/8" / 3.5 mm TRS Headphone Output Phantom Power +12 / 24 / 48V Plug-In Power Yes, 2.5 V Host Connection 1 x Mini-USB (USB 2.0) Gain Range 1/8" Inputs: Up to 52 dB Mic/Line Inputs: Up to 55 dB Max Input Level Mic/Line Inputs: +22 dBu (Pad On) Headphone Output Power 20 mW per Channel into 32 Ohms Microphone Sensitivity -45 dB/Pa 	2






PPC FEESION (AUSM THEORITY ACCOUNTABILITY

	•	
	 Microphone Max SPL 140 dB SPL Power Options Batteries, USB Bus Power, AC/DC Power Adapter Battery Type 2 x AA 	
:	 AC/DC Power Adapter 5 VDC at 1 A (Not Included) Dimensions 2.3 x 5.3 x 1.7" (Recorder) 2.6 x 2.4 x 1.6" (X/Y Mic) 	
	 Weight 6.2 oz (Recorder) 3.3 oz (Mic) 	
pcs	SD Card Reader	3
:	The UGREEN 2in1 card reader is designed for the highest data transfer speed, functionality, and compact design. Support for USB-C 3.1 port enables data transfer up to 5 Gb per second. The device is compatible with Windows (XP10), Mac	
	OS, and Linux operating systems. Thanks to Plug&Play technology, no additional software is required. The reader supports microSD and SD	
:	memory cards up to 512 GB. Premium production	
	The housing is made of high-quality aluminum,	
	which provides high strength, long life, and an	
	elegant appearance. Specification Model CM184	
	Plug-in USB-C 3.1 Material Aluminum Card slot	
	microSD + SD Data transmission rate to 5 Gb/s Max. supported memory 512 GB Supported formats Micro	
	SD, Micro SDXC, Micro SDHC, SD, SDXC, SDHC,	
:	MMC, RS-MMC, UHS-I Dimensions 61,5 x 21,5 x 11	
:	mm.	
pcs	SD CARD Extreme Pro 256gb (170mb/s) SDXC	3
	- Conseiltu 256 OD	
	Capacity: 256 GB Transfer Speeds up to 170MBPS	
	Compatible with SDXC and SDXC UHS-I enabled	
	host devices.	
	Dimension 24mm x 32mm x 2.1mm	
	 Product Weight 0.0016699999kgs 	
pcs	HOLLYLAND MARS 400S PRO	3
	Transcription and Description Oct	•
	Transmitter and Receiver Set Transmitter to 4000nS0 \	
-	 Transmit up to 1080p60 Video Transmit up to 400' to RX, 300' to App 	
	SDI and HDMI Inputs and Outputs	
	L-Series Battery/USB Type-C/DC Power	
	OLED Display, Low-Battery Warning	
	Extremely Low 0.1s Latency	
	Shoe Adapter & 1/4"-20 Mounting Thread	
	 Transmitter Panel Type and Receiver Panel Type: OLED 	
	1 x 1/4"-20 Female 1 x Cold Shoe	







	o x 2.8 x 1.32" / 11 x 7.2 x 3.35 cm	
	1 x Barrel (6 to 16 VDC up to 2 A) Input 1 x USB	
	Type-C (5 VDC up to 2 A) Input	
	Sony L-Series / NP-F Type (not included)	
pcs	Antenna-In Port	3
	Multimedia player - plays videos and music, browses files and photos	
	Personal video recorder	
	Nationwide emergency warning broadcast system	
	Functional auto-on alert feature	
	Measurements: L 17 x W 14 x H 4 cm	
1	• SSP-10082188	
pc	Digital Mixer	1
	Descrives often law major, high handrages and a	
	Premium ultra-low noise, high headroom analog mixer	
	2 state-of-the-art XENYX Mic Preamps comparable	
	to stand-alone boutique preamps	
	Studio-grade compressors with super-easy ?one-	
	knob? functionality and control LED for professional	
	vocal and instrumental sound	
	Ultra-high quality Klark Teknik FX processor with	
	100 presets including reverb, chorus, flanger, delay,	
	pitch shifter and various multi-effects	
	Built-in stereo USB/Audio Interface to connect	
	directly to your computer. Free audio recording,	
	editing and podcasting software plus 150	
	instrument/effect plug-ins downloadable at	
	behringer.com	
	 Neo-classic "British" 3-band EQs for warm and 	
	musical sound	
	FX send control per channel for internal FX	
	processor and/or as external send	
	 Main mix outputs plus separate control room, 	
	phones and 2-Track outputs	
	 2-Track inputs assignable to main mix or control 	
	room/phones outputs	
	3-Year Warranty Program*	
	Designed and engineered in Germany	
рс	FLUID TRIPOD 504HD,546BK 504 FLUID VIDEO HEAD	1
	& 546B ALU TWIN LEG TRIPOD	
	Weight: 217.62 oz	
	Collection/Series: 504	
	Material: Aluminum	
	 Safety Payload Weight: 26.46 lbs 	
	Min Height: 17.32 in	
	Maximum Height: 65.94 in	
	Head Type: Video/Fluid Head	





. !		
	 Leg Sections: 3 Legs Tube Diameter: 0.63- 0.98 in Quick Release: Yes Counterbalance System: Variable Steps Counterbalance Weight: 0- 5.51- 11.02- 16.53 lbs Center of gravity: 2.17 in Spreader: mid level – variable arm length: Closed Length: 33.07 in Ball Flat: 75 Ball Accessory Compatibility: MVAPANBARM; MVAPANBARL;502HLV; 509HLV; 114MV; 181B; 165MV Top Attachment: 1/4" screw, 3/8" screw Powered by (batteries): Lithium Bubble Spirit Level (No.): 1 Carrying Bag Included: MB MBAG100PN Center Column: no center column Certifications WEEE; RoHS Color: Black Easy Link: Yes Front Tilt: -60° / +90° Leg Type: Twin Leg Lock Type: Flip Lock Maximum Working Temperature: -20 Pan Bar Included: Yes Pan Drag: continuously adjustable from 0 to max level Panoramic Rotation 360 	
1 day	 Plate Type: 504PLONG Tilt Drag: continuously adjustable from 0 to max 	
pcs	level 90 Degree Micro HDMI to HDMI-compatible UP/Left/Right Angle Micro HDMI Cable for Digital camera (0.5 Meters)	2
	 Connector B: HDMI-CompatibleMini HDMI-CompatibleMicro HDMI-Compatible Gender: Male-Male Model Number: Micro HDMI-compatible Origin: CN(Origin) Type: HDMI-Compatible Cables Connector A: HDMI-CompatibleMini HDMI-CompatibleMicro HDMI-Compatible Package: No Feature: HDMI-Compatible1.4 Outer Diameter: micro hdmi 90 degree Bundle: Bundle 1 Packing: Polybag 	



PPOFECCIONALICAN MATERIAL ACCIONATARIATIVE



	Certification : NONE	
	Shielding : Braid	
pc	ULTRA THIN HDMI (TYPE A) TO MICRO HDMI (TYPE D) (0.5 Meters)	1
	Connector B : Micro HDMI (Type D)	
	Gender : Male-Male	
	Model Number : Micro HDMI-compatible	
pcs	HDMI Cable	3
-	(5 Meters)	
	Vention HDMI Cable enables you to connect HDMI	
	devices (e.g. PC, Laptop or Graphic Cards) to a monitor, display, projector, HDTV for video and	
	audio signal transfer.	
	Input port: HDMI	
	Output port: HDMI	
	Resolution: 4K @60Hz Max	
	Operating modes: mirror or extend mode for	
	choose;	
	Shell material: Injection Molding	
	Jacket material:PVC	
	Plug and play, no any driver or program required	·
pcs	NP-F970 L-Series Rechargeable Battery	6
	Power: 7.2 V, 47.4 Wh, 6,600 mAh	
	STAMINA super-long battery life	
	Lithium-ion Cells with No "Memory Effect"	
	Highly efficient, compact, and light-weight	
	Built-in Microprocessor communicates with camera,	
	and accurately indicates remaining battery time in	
	minutes.	
	Environmentally friendly: 100% free of lead,	
	cadmium, and mercury	
	Sony recommends you use only infoLITHIUM	
	batteries with products displaying the InfoLITHIUM	
	mark.	
	 Dimensions: W 38.2 x H 59.5 x D 55.6 mm 	
	Mass: approx. 225 g	
рc	NP-F970 Dual Channel Battery Charger	1
;	Battery Plate Type: LP-E6	
	Plug: US	
	 Input:AC 100V-240V 50/60Hz 1500mA (max.) 	
•	DC 12-24V 3000mA (min.)	
	Output Voltage: DC 8.4V/12.6V/16.8V	
	 Output Current:L 1000mA * 1, 500mA * 2 	
	o -H 1500mA * 1, 800mA *2	
	USB Output: 5V 2100mA	
	Item Size: 12.2 * 11 * 3cm / 4.8 * 4.3 * 1.2"	



MAKABAGONG ADUANA, MATATAG NA EKONOMIYA

ROFESSIONALISM INTEGRITY ACCC

 Item Size: 12.2 * 11 * 3cm / 4.8 * 4.3 * 1.2" Item Weight: 254.5g / 9.0oz 	
 Package Size: 17.8 * 12 * 4.8cm / 7 * 4.7 * 1.9" Package Weight: 378.5g / 13.3oz 	
Delivery Duration: Complete number of items and shall be delivered within Five (5) calendar days upon approval	8

Delivery Term/Duration:15 calendar days

Subject to Retention Money 1-5% Contract Amount

Interested suppliers are required to submit **original/certified true copy** of the following: 1) valid and current Mayor's Permit, (In case of expired MP/BP, Submit copy of recently expired permit and official receipt as proof of renewal), 2) DTI/SEC Registration (for partnerships/corporations, attach General Information Sheet & Articles of Incorporation), 3) PHILGEPS Registration Certificate, 4) Original Omnibus Sworn Statement, 5) Latest Income/Business Tax Return, and 6) duly signed price quotation form (Annex "A"). All must be properly signed and sealed. Must be submitted in hard copy.

Submission of quotation and eligibility documents is on or before **November 28**, 2022, 10:00 a.m., at General Services Division (GSD), Ground Floor, OCOM Building, Port Area, Manila.

Award of contract shall be made to the lowest quotation, which complies with the minimum description as stated above and other terms and conditions stated in the price quotation form.

Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative/s.

The BOC reserves the right to accept or reject any or all quotations and to impose additional terms and conditions as it may deem proper.

For inquiry, you may contact us at Telefax no. 8527-9757 or email us at bacsecretariat@customs.gov.ph.

Very truly yours,

ISAGANI D. GALSIM
Head, BAC Secretariat/
Chief Administrative Officer
General Services Division



PROFESSIONALIS!

ACCOUNTABILITY

PRICE QUOTATION FORM

Date

The Bids and Awards Committee Bureau of Customs Port Area, Manila

Project Title: Supply and Delivery of PIAD Equipment for Production and Documentation of OCOM Activities & Other BOC-Related Events

Sir/Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our quotation/s for the items as follows:

1LOT

Unit	Description	Qty	Unit Price	Total Price
pcs	 Number of Tracks 2 Max Sample Rate/Resolution 96 kHz / 24-Bit Microphone Built-In Cardioid Stereo Pair, X/Y Configuration Built-In Speaker Yes, 400 mW Mono Display LCD (Backlit) Memory Card Support SD, SDHC Audio File Formats BWF, MP3, WAV Sample Rates WAV: 44.1 / 48 / 96 kHz (Stereo) MP3: 44.1 kHz Bit Depth 16/24-Bit Bit Rates 48 to 320 kb/s 48 to 320 kb/s Timecode No Analog I/O 1 x 1/8" / 3.5 mm TRS Line/Mic Input 2 x Combo XLR / 1/4" TRS Input 1 x 1/8" / 3.5 mm TRS Line Output 1 x 1/8" / 3.5 mm TRS Line Output 1 x 1/8" / 3.5 mm TRS Headphone Output Phantom Power +12 / 24 / 48V Plug-In Power Yes, 2.5 V Host Connection 1 x Mini-USB (USB 2.0) 	2		



MAKABAGONG ADUANA, MATATAG NA EKONOMIYA

Gain Range 1/8" Inputs: Up to 52 dB | Mic/Line Inputs: Up to 55 dB Max Input Level Mic/Line Inputs: +22 dBu (Pad On) Headphone Output Power 20 mW per Channel into 32 Ohms Microphone Sensitivity -45 dB/Pa Microphone Max SPL 140 dB SPL Power Options Batteries, USB Bus Power, AC/DC Power Adapter Battery Type 2 x AA AC/DC Power Adapter 5 VDC at 1 A (Not Included) Dimensions 2.3 x 5.3 x 1.7" (Recorder) | 2.6 x 2.4 x 1.6" (X/Y Mic) Weight 6.2 oz (Recorder) | 3.3 oz (Mic) SD Card Reader pcs The UGREEN 2in1 card reader is designed for the highest data transfer speed, functionality, and compact design. Support for USB-C 3.1 port enables data transfer up to 5 Gb per The second. device compatible with Windows (XP...10), Mac OS, and Linux operating systems. Thanks to Plug&Play technology, additional software is required. The reader supports microSD and SD memory cards up to 512 GB. Premium production The housing is made of highquality aluminum, which provides high strength, long life, and an elegant appearance. Specification Model CM184 Plug-in USB-C 3.1 Material Aluminum Card slot microSD + SD Data transmission rate to 5

Gb/s Max. supported memory 512 GB Supported formats





	Micro SD, Micro SDXC, Micro SDHC, SD, SDXC, SDHC, MMC, RS-MMC, UHS-I Dimensions 61,5 x 21,5 x 11 mm.	
pcs	SD CARD Extreme Pro 256gb (170mb/s) SDXC Capacity: 256 GB Transfer Speeds up to 170MBPS Compatible with SDXC and SDXC UHS-I enabled host devices. Dimension 24mm x 32mm x 2.1mm Product Weight 0.0016699999kgs	3
pcs	Transmitter and Receiver Set Transmit up to 1080p60 Video Transmit up to 400' to RX, 300' to App SDI and HDMI Inputs and Outputs L-Series Battery/USB Type-C/DC Power OLED Display, Low-Battery Warning Extremely Low 0.1s Latency Shoe Adapter & 1/4"-20 Mounting Thread Transmitter Panel Type and Receiver Panel Type: OLED 1 x 1/4"-20 Female 1 x Cold Shoe x 2.8 x 1.32" / 11 x 7.2 x 3.35 cm 1 x Barrel (6 to 16 VDC up to 2 A) Input 1 x USB Type-C (5 VDC up to 2 A) Input Sony L-Series / NP-F Type (not included)	3
pcs	Antenna-In Port Multimedia player - plays videos and music, browses files and photos • Personal video recorder	3





	 Nationwide emergency warning broadcast system Functional auto-on alert feature Measurements: L 17 x W 14 x H 4 cm SSP-10082188 	
рс	Premium ultra-low noise, high headroom analog mixer 2 state-of-the-art XENYX Mic Preamps comparable to standalone boutique preamps Studio-grade compressors with super-easy ?one-knob? functionality and control LED for professional vocal and instrumental sound Ultra-high quality Klark Teknik FX processor with 100 presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects Built-in stereo USB/Audio Interface to connect directly to your computer. Free audio recording, editing and podcasting software plus 150 instrument/effect plug-ins downloadable at behringer.com Neo-classic "British" 3-band EQs for warm and musical sound FX send control per channel for internal FX processor and/or as external send Main mix outputs plus separate control room, phones and 2-Track outputs 2-Track inputs assignable to main mix or control room/phones outputs 3-Year Warranty Program* Designed and engineered in Germany	
pc	FLUID TRIPOD 504HD,546BK 504 FLUID VIDEO HEAD & 546B ALU TWIN LEG TRIPOD	1



MAKABAGONG ADUANA, MATATAG NA EKONOMIYA



PROFESSIONALISM

ACCOUNTABILITY

0	Weight: 217.62 oz
0	Collection/Series: 504

Material: Aluminum

 Safety Payload Weight: 26.46 lbs

• Min Height: 17.32 in

• Maximum Height: 65.94 in

Head Type: Video/Fluid Head

Leg Sections: 3

Legs Tube Diameter: 0.63- 0.98

· Quick Release: Yes

 Counterbalance System: Variable Steps

 Counterbalance Weight: 0-5.51- 11.02- 16.53 lbs

· Center of gravity: 2.17 in

 Spreader: mid level – variable arm length

Closed Length: 33.07 in

Ball Flat: 75 Ball

 Accessory Compatibility: MVAPANBARM; MVAPANBARL;502HLV; 509HLV; 114MV; 181B; 165MV

 Top Attachment: 1/4" screw, 3/8" screw

Powered by (batteries): Lithium

Bubble Spirit Level (No.): 1

Carrying Bag Included: MB MBAG100PN

 Center Column: no center column

Certifications WEEE; RoHS

· Color: Black

Easy Link: Yes

Front Tilt: -60° / +90°

Leg Type: Twin

Leg Lock Type: Flip Lock

 Maximum Working Temperature: 60

 Minimum Working Temperature: -20

Pan Bar Included: Yes

 Pan Drag: continuously adjustable from 0 to max level

Panoramic Rotation 360

Plate Type: 504PLONG

Tilt Drag: continuously adjustable from 0 to max level

A Modernized and Credible Customs Administration That is Among the World's Best South Harbor, Gate 3, Port Area, Manila 1099




pcs	90 Degree Micro HDMI to HDMI- compatible UP/Left/Right Angle Micro HDMI Cable for Digital camera (0.5 Meters)	2	
	 Connector B: HDMI- CompatibleMini HDMI- CompatibleMicro HDMI- Compatible Gender: Male-Male Model Number: Micro HDMI- compatible Origin: CN(Origin) Type: HDMI-Compatible Cables Connector A: HDMI- CompatibleMini HDMI- CompatibleMicro HDMI- Compatible Package: No Feature: HDMI-Compatible1.4 Outer Diameter: micro hdmi 90 degree Bundle: Bundle 1 Packing: Polybag Certification: NONE 		
рс	ULTRA THIN HDMI (TYPE A) TO MICRO HDMI (TYPE D) (0.5 Meters) • Connector B : Micro HDMI (Type D) • Gender : Male-Male • Model Number : Micro HDMI-compatible	1	
pcs	HDMI Cable (5 Meters) Vention HDMI Cable enables you to connect HDMI devices (e.g. PC, Laptop or Graphic Cards) to a monitor, display, projector, HDTV for video and audio signal transfer. Input port: HDMI Output port: HDMI Resolution: 4K @60Hz Max Operating modes: mirror or extend mode for choose;	3	





	 Shell material: Injection Molding Jacket material:PVC Plug and play, no any driver or program required 	
pcs	NP-F970 L-Series Rechargeable Battery Power: 7.2 V, 47.4 Wh, 6,600 mAh STAMINA super-long battery life Lithium-ion Cells with No "Memory Effect" Highly efficient, compact, and light-weight Built-in Microprocessor communicates with camera, and accurately indicates remaining battery time in minutes. Environmentally friendly: 100% free of lead, cadmium, and mercury Sony recommends you use only InfoLITHIUM batteries with products displaying the InfoLITHIUM mark. Dimensions: W 38.2 x H 59.5 x D 55.6 mm Mass: approx. 225 g	6
рс	NP-F970 Dual Channel Battery Charger Battery Plate Type: LP-E6 Plug: US Input:AC 100V-240V 50/60Hz 1500mA (max.)DC 12-24V 3000mA (min.) Output Voltage: DC 8.4V/12.6V/16.8V Output Current:L 1000mA * 1, 500mA * 2H 1500mA * 1, 800mA *2 USB Output: 5V 2100mA Item Size: 12.2 * 11 * 3cm / 4.8 * 4.3 * 1.2" Item Weight: 254.5g / 9.0oz	







Package Size: 17.8 * 12 * 4.8cm / 7 * 4.7 * 1.9" Package Weight: 378.5g / 13.3oz **Delivery Duration:** Complete number of items and shall be delivered within Five (5) calendar days upon approval **TOTAL** Total amount in words: Delivery Term/Duration: 5 calendar days Subject to Retention Money 1-5% Contract Amount The above-quoted prices are inclusive of all costs and applicable taxes. Very truly yours, Name/ Signature of Representative Name of Company Contact No. Mayor's Permit No. PhilGEPS Registration No._ (Please submit the photocopies of the above documents upon submission of quotation)