



REPUBLIC OF THE PHILIPPINES  
DEPARTMENT OF FINANCE  
**BUREAU OF CUSTOMS**

*A modernized and credible customs administration that upholds good governance and is among the world's best*

### REQUEST FOR QUOTATION

The Bureau of Customs (BOC), through its Administration Office (AO), will undertake a Small Value Procurement for **“Supply and Delivery of Sound System with Components and Accessories”** in accordance with the Revised Implementing Rules and Regulations of Republic Act No. 9184. The details of the project are as follows:

Name of Project: **Supply and Delivery of Sound System with Components and Accessories**

Location: **General Services Division, OCOM Building, Gate 3, South Harbor, Port Area, Manila**

Approved Budget for the Contract: **Five Hundred Twenty-Three Thousand Seven Hundred Twenty-Nine Pesos and 50/100 (Php523,729.50) - inclusive of tax**

Specifications :

UNIT	ITEM DESCRIPTION	QUANTITY
Set	<b>Professional Audio Mixer 16-channel</b> <ul style="list-style-type: none"><li>• Auto Volt 110v to 220v</li><li>• 16 High headroom line input</li><li>• 3 Band EQ</li><li>• Mute &amp; Solo function</li><li>• 48V Phantom Power</li><li>• 2 Aux output</li><li>• 75Hz low-cut filter for Mic/Line input channels</li><li>• Sealed rotary controls resist dust &amp; grime</li><li>• 24 Bit 99 DSP digital effects</li><li>• Large display for better visibility</li><li>• 12 Mic/Line, 2 Stereo input</li><li>• 12 segment stereo LED meter</li><li>• Headphones and foot switch</li><li>• Bluetooth/USB/MP3 with REC function</li></ul>	1
Set	<b>Sonic Audio Maximizer</b> <ul style="list-style-type: none"><li>• Signal to Noise Ratio: 115dB Process IN</li><li>• Process Mode: Program controlled</li><li>• Bypass Mode: 10Hz to 50kHz, +/- 0.5dBu, 0dBu input</li><li>• Output Impedance: 600 Ohms, balanced 1/4" stereo phone jack or XLR jack. Pin #2 is the hot or "+" signal.</li><li>• THD, Process mode: less than 0.025% 20-20kHz</li><li>• Bypass mode: less than 0.002% 20-20kHz</li></ul>	2



Gate 3, South Harbor, Port Area, Manila 1018

+63 (02) 8705-6000, +63 (02) 8527-1968 | [www.customs.gov.ph](http://www.customs.gov.ph) | [boc.cares@customs.gov.ph](mailto:boc.cares@customs.gov.ph)

	<ul style="list-style-type: none"> <li>Maximum Output: +23dBu (may vary due to control settings)</li> <li>Maximum Process: +12dBu boost at 5kHz, 0dBu input</li> <li>Sensitivity: -45dBu for maximum process</li> <li>Lo Contour: +12dBu adjustment at 50Hz, 0dBu input</li> <li>Input Impedance: 14.7K Ohms, balanced 1/4" stereo phone jack or XLR jack. Pin #2 is the hot or "+" signal.</li> </ul>	
set	<b>Dual Channel Active Crossover</b> <ul style="list-style-type: none"> <li>Operating Voltage: 220V 50-60Hz</li> <li>Input Type: Electronically balance/unbalances, RF filtered</li> <li>Input Impedance: Balance 50, Unbalanced 25</li> <li>Phase Invert Switch: Inverts the phase at the output, one switch per output</li> <li>Output Impedance: Balance 60, Unbalanced 30</li> <li>Bandwidth: 20Hz – 20Hz</li> <li>Frequency Response: 3Hz to 80KHz</li> <li>S/N ratio: ≥94dB (low), ≥93dB (mid), ≥90dB (high) output</li> <li>Mode Switch: Selects stereo/mono2/2/4-way operation</li> <li>Dimension (HxWxD): 4.4(H) x 48(W) x 17.5(D)cm</li> <li>THD: ≤0.004%</li> <li>Interchannel crosstalk: ≤81dB</li> <li>Low cut Switch: 40Hz 12dB/octave Bessel high-pass filter, one switch per channel</li> <li>Dynamic Range: ≥108dB</li> </ul>	1
Set	<b>Dual Channel 31-Band Equalizer</b> <ul style="list-style-type: none"> <li>Input Type: Electronically balance/unbalances, RF filtered</li> <li>Input Impedance: Balance 40, Unbalanced 20</li> <li>Output Impedance: Balance 100, Unbalanced 50</li> <li>Bandwidth: 20Hz – 20Hz</li> <li>Frequency Response: 10Hz to 50KHz</li> <li>S/N ratio: ≥94dB</li> <li>THD: ≤0.005%</li> <li>Dimension (HxWxD): 13.4(H) x 48(W) x 20(D)cm</li> <li>Low cut Switch: 40Hz 18dB/octave Bessel high-pass filter</li> <li>Intercanal crosstalk: ≤81dB</li> <li>Dynamic Range: ≥108dB</li> <li>Operating Voltage: 220V 50-60Hz</li> <li>Bypass Switch: Bypasses thru signal path</li> <li>Range Switch: +/-6 dB or +/-15dB slider boost/cut range</li> </ul>	2
Set	<b>1500W Professional Power Amplifier (Low AMP)</b> <ul style="list-style-type: none"> <li>8 Ohms Bridged Mono Power: 3200W times 2</li> <li>4 Ohms Bridged Mono Power, 20Hz-20kHz, 0.1% THD+N: 4400W</li> <li>Max RMS Output Voltage (each Channel): 100V</li> <li>Max Peak Output Voltage: 130V</li> </ul>	1



	<ul style="list-style-type: none"> <li>• Frequency Response (+0/-0.3dB,1W/8Ohms): 20Hz-20KHz</li> <li>• Power Bandwidth (rated power at 4Ohms, 1%THD+N): 20Hz-20KHz</li> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09%</li> <li>• 1200Wx2 8 Ohms</li> <li>• Input CMRR (1kHz) :&gt;-60dB</li> <li>• Standard Input Sensitivity (rated power at 8 Ohms): 0.775V/1V/1.4V</li> <li>• Hum and Noise ('A" weighted, full power at 8 Ohms): -102dB</li> <li>• Power Supply (Factory Configured): 220V-240V, 50Hz-60Hz</li> <li>• Construction: Integrated stencil plate</li> <li>• Dimension HXWXL: 133x483x505mm</li> <li>• Powered Amplifier with Mosfet Transistor</li> <li>• Input Impedance (balanced/unbalanced): &gt;10K/&gt;20K</li> <li>• Standard Voltage Gain (rated power at 8 Ohms): X80</li> <li>• Output Connectors (per channel): 2-way binding posts or speak on connectors (market dependent)</li> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09%</li> <li>• Damping Factor (10-400Hz at 8 Ohms): 460</li> </ul>	
Set	<p><b>1000W Professional Power Amplifier (Mid AMP)</b></p> <ul style="list-style-type: none"> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09%</li> <li>• 8 Ohms Bridged Mono Power: 3000W</li> <li>• 4 Ohms Bridged Mono Power, 20Hz-20kHz, 0.1% THD+N: 4100W</li> <li>• Max RMS Output Voltage (each Channel): 90V</li> <li>• Max Peak Output Voltage: 120V</li> <li>• Frequency Response (+0/-0.3dB,1W/8Ohms): 20Hz-20KHz</li> <li>• Power Bandwidth (rated power at 4Ohms, 1%THD+N): 20Hz-20KHz</li> <li>• 1000Wx2 8 Ohms</li> <li>• Input CMRR (1kHz) :&gt;-60dB</li> <li>• Standard Input Sensitivity (rated power at 8 Ohms): 0.775V/1V/1.4V</li> <li>• Hum and Noise ('A" weighted, full power at 8 Ohms): -102dB</li> <li>• Construction: Integrated stencil plate</li> <li>• Power Supply (Factory Configured): 220V-240V, 50Hz-60Hz</li> <li>• Dimension HXWXL: 133x483x505mm</li> <li>• Powered Amplifier with Mosfet Transistor</li> <li>• Input Impedance (balanced/unbalanced): &gt;10K/&gt;20K</li> <li>• Standard Voltage Gain (rated power at 8 Ohms): X80</li> <li>• Damping Factor (10-400Hz at 8 Ohms): 430</li> <li>• Crosstalk ('A" weighted, full power at 8 Ohms): -60dB</li> </ul>	1

	<ul style="list-style-type: none"> <li>Output Connectors (per channel): 2-way binding posts or speak on connectors (market dependent)</li> </ul>	
Set	<b>18" Subwoofer Speaker (Base) – Active</b> <ul style="list-style-type: none"> <li>Active</li> <li>Subwoofer: 18inch</li> <li>Fre. Response: 75Hz-180Hz</li> <li>Minimum Power: 800W</li> <li>Maximum Power: 1000W</li> <li>Impedance: 4-8 Ohms</li> <li>Sensitivity: 95dB+3dB</li> </ul>	2
Set	<b>18" Subwoofer Speaker (Base) – Passive</b> <ul style="list-style-type: none"> <li>Passive</li> <li>Subwoofer: 18inch</li> <li>Freq. Response: 35Hz-200Hz</li> <li>Minimum Power: 800W</li> <li>Maximum Power: 1000W</li> <li>Impedance: 4-8 Ohms</li> <li>Sensitivity: 95dB+3dB</li> </ul>	2
Set	<b>15" Active Loudspeaker (Mid) w/ Professional Hi-Fi (tweeter) Speaker w/ Stand</b> <ul style="list-style-type: none"> <li>LF: 3" Voice Coil Size</li> <li>System Type: 15" 2 Way</li> <li>Amp. Power: 500 Max</li> <li>Output Connector: Line (XLR)</li> <li>Impedance: 8Ω</li> <li>Freq. Response: 38Hz-20Khz</li> <li>Input Connector: Line (XLR)</li> <li>Output: 1 Microphone</li> <li>Input: RCA</li> <li>Sensitivity: 100dB</li> <li>1000W Peak Power/500W Class D</li> <li>HF: 1.7" Voice Coil Size</li> </ul>	2
Set	<b>15" Passive Loudspeaker (Mid) w/ Professional Hi-Fi (tweeter) Speaker w/ Stand</b> <ul style="list-style-type: none"> <li>1000W Peak Power/500W Class D</li> <li>System Type: 15" 2 Way</li> <li>Power: 1000W</li> <li>Inputs: 2 NL4 Speakon</li> <li>LF: 3" Voice Coil</li> <li>HF: 1.7" Polymide Dome Tweeter</li> <li>Impedance: 8Ω</li> <li>Enclosure:ABS Plastic Material</li> <li>Sensitivity: 99dB</li> <li>Frequency Response: 43Hz-20KHz</li> <li>Air Duct: Front</li> </ul>	4

Set	<b>Input/Output XLR Cable Connector</b> <ul style="list-style-type: none"> <li>• Input/Output</li> <li>• 3P XLR Female + 3P XLR Male</li> <li>• XLR Connector</li> </ul>	50
Set	<b>Wired Microphone</b> <ul style="list-style-type: none"> <li>• Sensitivity mvpa: 2.50</li> <li>• Height (mm) / (in): 173.8mm / 6.846 in</li> <li>• Width (mm) / (in): 52.6 mm / 2.071 in</li> <li>• Depth (mm) / (in): 52.6 mm / 2.071 in</li> <li>• Transducer Type: Dynamic</li> <li>• Polar Pattern: Cardioid</li> <li>• Sensitivity dBV/Pa: -52.00</li> <li>• Frequency Range To (kHz): 15</li> <li>• Impedance (Ω): 600</li> <li>• Frequency Range From (Hz): 50</li> <li>• Weight (g) / (lbs): 244g / 0.494 lbs</li> </ul>	4
Set	<b>Microphone Stand</b> <ul style="list-style-type: none"> <li>• Material: Metal Base</li> <li>• Height Adjustment: Adjustable from 1080mm to 1750mm</li> <li>• Base: Weighted base for stability</li> <li>• Type: Heavy Duty microphone stand</li> </ul>	4
Set	<b>Wireless Microphone</b> <ul style="list-style-type: none"> <li>• Wireless Microphone (1 receiver 2 wireless microphone)</li> <li>• Type: UHF Wireless Microphone System</li> <li>• Frequency Range: 610-670 Mhz</li> <li>• Number of Channels: 200</li> <li>• Transmission Range: Up to 200 meters</li> <li>• Frequency Matching: Infrared (IR)</li> <li>• Pilot Mode: Pilot and digital ID</li> <li>• Microphone Body: Metal</li> <li>• True Diversity Dual UHF Microphone 200m</li> <li>• Receiver Power: 220V/50Hz</li> <li>• Tru Diversity: Yes</li> <li>• Total Harmonic Distortion: &lt;0.5%</li> </ul>	2
Set	<b>XLR Cable (100M)</b> <ul style="list-style-type: none"> <li>• Ground with Cotton Shield</li> <li>• 3 Conductors</li> <li>• Double Shield</li> <li>• Microphone Cable</li> <li>• Audio Cable</li> <li>• Good Copper Screen</li> <li>• OD: 6.7mm (100M)</li> <li>• Microphone Cable</li> </ul>	5



Set	<b>Portable Rechargeable Powered Speaker with Wireless Microphone</b> <ul style="list-style-type: none"> <li>• Sensitivity: 98dB</li> <li>• LF: 12" Woofer (2" Voice coil size)</li> <li>• HF: 1.5 Titanium Dome Tweeter</li> <li>• Freq. Resp.: 45Hz-20kHz</li> <li>• AC Input: 220V 50-60Hz</li> <li>• Amp. Power: 450W MAX</li> <li>• Impedance: 4 ohms</li> <li>• Input Gain: line: +20 dBu/ Mic: +40dB</li> <li>• Input Connector: Line (XLR, RCA &amp; PL), Mic (PL &amp; XLR)</li> <li>• Dimension (HxWxD): 122(H) x 37(W) x 33(D)cm</li> <li>• System Type: 12" 2 Way Full Range</li> <li>• Signal indicator: Limit, Clip</li> <li>• Crossover Freq.: 3KHz</li> <li>• Output Connector: Line (XLR &amp; PL link out), Speaker (Speakon to passive speaker)</li> </ul>	2
Set	<b>20K VA Automatic Voltage Regulator (AVR)</b> <ul style="list-style-type: none"> <li>• Capacity: 20,000 VA (20KVA)</li> <li>• Phase Type: Single Phase (AVR)</li> <li>• Voltage Input Range: 140V to 250V</li> <li>• Voltage Output: 220V</li> <li>• Voltage Stabilization Accuracy: 220V <math>\pm</math>3</li> <li>• Over-Voltage Protection Value: 246V <math>\pm</math>4V</li> <li>• Under-Voltage Indication Value: 186V <math>\pm</math>4V</li> <li>• Load Power Factor: 0.8</li> <li>• Adjusting Time: 1.5 seconds</li> <li>• Long Delay: 5 <math>\pm</math>2 minutes for startup safety.</li> <li>• Short Delay: 5 <math>\pm</math>2 seconds for quicker voltage response.</li> <li>• Insulation Resistance: 5 M<math>\Omega</math>.</li> <li>• Winding Material: 100% pure copper winding</li> <li>• True Output Power: 100% true output power</li> </ul>	1
Set	<b>Audio Rack Cabinet</b> <ul style="list-style-type: none"> <li>• MC-14U</li> <li>• Proc case with mixer on top with wheel</li> <li>• Original IMIX/Trident Proc case</li> </ul>	1
Set	<b>Power Distribution Unit (PDU)</b> <ul style="list-style-type: none"> <li>• Front 8-position switch</li> <li>• Sub-control Switch : Yes</li> <li>• Surge Protector : Yes</li> <li>• Back 8 16A-socket output</li> <li>• Overload Protection : Yes</li> <li>• Type: Extension Sock</li> <li>• With cover (front switch)</li> <li>• Grounding: Standard Grounding</li> <li>• Voltage: 220-250V</li> </ul>	1

Set	<b>Wire Speaker</b> <ul style="list-style-type: none"> <li>• Cable Size: 14 AWG</li> <li>• 2 x 2.5mm<sup>2</sup></li> <li>• Cable Color: Black</li> <li>• Cable Length: 100M</li> <li>• Professional Speaker Wire</li> </ul>	2
-----	--	---

**Delivery Term/Duration: 20 calendar days**

Subject to Retention Money

Interested suppliers are required to submit **original/certified true copy** of the following: 1) valid and current Mayor's/Business Permit, (In case of expired MP/BP, submit copy of recently expired permit and official receipt as proof of renewal), 2) PHILGEPS Registration Number, 3) Latest Income/Business Tax Return 4) Original duly signed Omnibus Sworn Statement (OSS) 5) Duly signed price quotation form (Annex "A"). In case of goods kindly indicate the brand being offered in your price quotation form (Annex "A")

**All must be properly signed and sealed. Must be submitted in hard copy.** Submission of quotation and eligibility documents is on or before **July 11, 2025, 10:00 a.m., at General Services Division (GSD), Ground Floor, OCOM Building, Port Area, Manila.**

Award of contract shall be made to the lowest quotation, which complies with the minimum description as stated above and other terms and conditions stated in the price quotation form.

Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative/s.

The BOC reserves the right to accept or reject any or all quotations and to impose additional terms and conditions as it may deem proper.

For inquiry, you may contact us at Telefax no. 8526-6571 or email us at [boc-svp@customs.gov.ph](mailto:boc-svp@customs.gov.ph).

Very truly yours,



**RAQUEL G. DE JESUS**

Head, BAC Secretariat/

Acting Chief, General Services Division



Gate 3, South Harbor, Port Area, Manila 1018

+63 (02) 8705-6000, +63 (02) 8527-1968 | [www.customs.gov.ph](http://www.customs.gov.ph) | [boc.cares@customs.gov.ph](mailto:boc.cares@customs.gov.ph)

Annex "A"

**PRICE QUOTATION FORM**

Date:

The Bids and Awards Committee  
Bureau of Customs  
Port Area, Manila

Project Title: **Supply and Delivery of Sound System with Components and Accessories**

Sir/Madam:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our quotation/s for the items as follows:

UNIT	ITEM DESCRIPTION	QUANTITY	UNIT COST	TOTAL COST
Set	<b>Professional Audio Mixer 16-channel</b> <ul style="list-style-type: none"> <li>• Auto Volt 110v to 220v</li> <li>• 16 High headroom line input</li> <li>• 3 Band EQ</li> <li>• Mute &amp; Solo function</li> <li>• 48V Phantom Power</li> <li>• 2 Aux output</li> <li>• 75Hz low-cut filter for Mic/Line input channels</li> <li>• Sealed rotary controls resist dust &amp; grime</li> <li>• 24 Bit 99 DSP digital effects</li> <li>• Large display for better visibility</li> <li>• 12 Mic/Line, 2 Stereo input</li> <li>• 12 segment stereo LED meter</li> <li>• Headphones and foot switch</li> <li>• Bluetooth/USB/MP3 with REC function</li> </ul>	1		
Set	<b>Sonic Audio Maximizer</b> <ul style="list-style-type: none"> <li>• Signal to Noise Ratio: 115dB Process IN</li> <li>• Process Mode: Program controlled</li> <li>• Bypass Mode: 10Hz to 50kHz, +/- 0.5dBu, 0dBu input</li> <li>• Output Impedance: 600 Ohms, balanced 1/4" stereo phone jack or XLR jack. Pin #2 is the hot or "+" signal.</li> </ul>	2		





	<ul style="list-style-type: none"> <li>• THD, Process mode: less than 0.025% 20-20kHz</li> <li>• Bypass mode: less than 0.002% 20-20kHz</li> <li>• Maximum Output: +23dBu (may vary due to control settings)</li> <li>• Maximum Process: +12dBu boost at 5kHz, 0dBu input</li> <li>• Sensitivity: -45dBu for maximum process</li> <li>• Lo Contour: +12dBu adjustment at 50Hz, 0dBu input</li> </ul> <p>Input Impedance: 14.7K Ohms, balanced 1/4" stereo phone jack or XLR jack. Pin #2 is the hot or "+" signal.</p>			
Set	<p><b>Dual Channel Active Crossover</b></p> <ul style="list-style-type: none"> <li>• Operating Voltage: 220V 50-60Hz</li> <li>• Input Type: Electronically balance/unbalances, RF filtered</li> <li>• Input Impedance: Balance 50, Unbalanced 25</li> <li>• Phase Invert Switch: Inverts the phase at the output, one switch per output</li> <li>• Output Impedance: Balance 60, Unbalanced 30</li> <li>• Bandwidth: 20Hz – 20KHz</li> <li>• Frequency Response: 3Hz to 80KHz</li> <li>• S/N ratio: ≥94dB (low), ≥93dB (mid), ≥90dB (high) output</li> <li>• Mode Switch: Selects stereo/mono2/2/4-way operation</li> <li>• Dimension (HxWxD): 4.4(H) x 48(W) x 17.5(D)cm</li> <li>• THD: ≤0.004%</li> <li>• Interchannel crosstalk: ≤81dB</li> <li>• Low cut Switch: 40Hz 12dB/octave Bessel high-pass filter, one switch per channel</li> <li>• Dynamic Range: ≥108dB</li> </ul>	1		
Set	<p><b>Dual Channel 31-Band Equalizer</b></p> <ul style="list-style-type: none"> <li>• Input Type: Electronically balance/unbalances, RF filtered</li> </ul>	2		

	<ul style="list-style-type: none"> <li>• Input Impedance: Balance 40, Unbalanced 20</li> <li>• Output Impedance: Balance 100, Unbalanced 50</li> <li>• Bandwidth: 20Hz – 20KHz</li> <li>• Frequency Response: 10Hz to 50KHz</li> <li>• S/N ratio: ≥94dB</li> <li>• THD: ≤0.005%</li> <li>• Dimension (HxWxD): 13.4(H) x 48(W) x 20(D)cm</li> <li>• Low cut Switch: 40Hz 18dB/octave Bessel high-pass filter</li> <li>• Intercanal crosstalk: ≤81dB</li> <li>• Dynamic Range: ≥108dB</li> <li>• Operating Voltage: 220V 50-60Hz</li> <li>• Bypass Switch: Bypasses thru signal path</li> <li>• Range Switch: +/-6 dB or +/-15dB slider boost/cut range</li> </ul>			
Set	<p><b>1500W Professional Power Amplifier (Low AMP)</b></p> <ul style="list-style-type: none"> <li>• 8 Ohms Bridged Mono Power: 3200W times 2</li> <li>• 4 Ohms Bridged Mono Power, 20Hz-20kHz, 0.1% THD+N: 4400W</li> <li>• Max RMS Output Voltage (each Channel): 100V</li> <li>• Max Peak Output Voltage: 130V</li> <li>• Frequency Response (+0/-0.3dB, 1W/8Ohms): 20Hz-20KHz</li> <li>• Power Bandwidth (rated power at 4Ohms, 1%THD+N): 20Hz-20KHz</li> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09%</li> <li>• 1200Wx2 8 Ohms</li> <li>• Input CMRR (1kHz) :&gt;-60dB</li> <li>• Standard Input Sensitivity (rated power at 8 Ohms): 0.775V/1V/1.4V</li> <li>• Hum and Noise ('A" weighted, full power at 8 Ohms): -102dB</li> </ul>	1		

	<ul style="list-style-type: none"> <li>• Power Supply (Factory Configured): 220V-240V, 50Hz-60Hz</li> <li>• Construction: Integrated stencil plate</li> <li>• Dimension HXWXL: 133x483x505mm</li> <li>• Powered Amplifier with Mosfet Transistor</li> <li>• Input Impedance (balanced/unbalanced): &gt;10K/&gt;20K</li> <li>• Standard Voltage Gain (rated power at 8 Ohms): X80</li> <li>• Output Connectors (per channel): 2-way binding posts or speak on connectors (market dependent)</li> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09% Damping Factor (10-400Hz at 8 Ohms): 460</li> </ul>			
Set	<p><b>1000W Professional Power Amplifier (Mid AMP)</b></p> <ul style="list-style-type: none"> <li>• THD+N (rated power, 4Ohms/1kHz): &lt;0.09%</li> <li>• 8 Ohms Bridged Mono Power: 3000W</li> <li>• 4 Ohms Bridged Mono Power, 20Hz-20kHz, 0.1% THD+N: 4100W</li> <li>• Max RMS Output Voltage (each Channel): 90V</li> <li>• Max Peak Output Voltage: 120V</li> <li>• Frequency Response (+0/-0.3dB, 1W/8Ohms): 20Hz-20KHz</li> <li>• Power Bandwidth (rated power at 4Ohms, 1%THD+N): 20Hz-20KHz</li> <li>• 1000Wx2 8 Ohms</li> <li>• Input CMRR (1kHz) :&gt;-60dB</li> <li>• Standard Input Sensitivity (rated power at 8 Ohms): 0.775V/1V/1.4V</li> <li>• Hum and Noise ('A" weighted, full power at 8 Ohms): -102dB</li> <li>• Construction: Integrated stencil plate</li> </ul>	1		



	<ul style="list-style-type: none"> <li>• Power Supply (Factory Configured): 220V-240V, 50Hz-60Hz</li> <li>• Dimension HXWXL: 133x483x505mm</li> <li>• Powered Amplifier with Mosfet Transistor</li> <li>• Input Impedance (balanced/unbalanced): &gt;10K/&gt;20K</li> <li>• Standard Voltage Gain (rated power at 8 Ohms): X80</li> <li>• Damping Factor (10-400Hz at 8 Ohms): 430</li> <li>• Crosstalk ('A" weighted, full power at 8 Ohms): -60dB</li> <li>• Output Connectors (per channel): 2-way binding posts or speak on connectors (market dependent)</li> </ul>			
Set	<b>18" Subwoofer Speaker (Base) – Active</b> <ul style="list-style-type: none"> <li>• Active</li> <li>• Subwoofer: 18inch</li> <li>• Fre. Response: 75Hz-180Hz</li> <li>• Minimum Power: 800W</li> <li>• Maximum Power: 1000W</li> <li>• Impedance: 4-8 Ohms</li> <li>• Sensitivity: 95dB+3dB</li> </ul>	2		
Set	<b>18" Subwoofer Speaker (Base) – Passive</b> <ul style="list-style-type: none"> <li>• Passive</li> <li>• Subwoofer: 18inch</li> <li>• Freq. Response: 35Hz-200Hz</li> <li>• Minimum Power: 800W</li> <li>• Maximum Power: 1000W</li> <li>• Impedance: 4-8 Ohms</li> <li>• Sensitivity: 95dB+3dB</li> </ul>	2		
Set	<b>15" Active Loudspeaker (Mid) w/ Professional Hi-Fi (tweeter) Speaker w/ Stand</b> <ul style="list-style-type: none"> <li>• LF: 3" Voice Coil Size</li> <li>• System Type: 15" 2 Way</li> <li>• Amp. Power: 500 Max</li> <li>• Output Connector: Line (XLR)</li> <li>• Impedance: 8Ω</li> <li>• Freq. Response: 38Hz-20Khz</li> <li>• Input Connector: Line (XLR)</li> </ul>	2		

	<ul style="list-style-type: none"> <li>• Output: 1 Microphone</li> <li>• Input: RCA</li> <li>• Sensitivity: 100dB</li> <li>• 1000W Peak Power/500W Class D</li> <li>• HF: 1.7" Voice Coil Size</li> </ul>			
Set	<b>15" Passive Loudspeaker (Mid) w/ Professional Hi-Fi (tweeter) Speaker w/ Stand</b> <ul style="list-style-type: none"> <li>• 1000W Peak Power/500W Class D</li> <li>• System Type: 15" 2 Way</li> <li>• Power: 1000W</li> <li>• Inputs: 2 NL4 Speakon</li> <li>• LF: 3" Voice Coil</li> <li>• HF: 1.7" Polymide Dome Tweeter</li> <li>• Impedance: 8Ω</li> <li>• Enclosure: ABS Plastic Material</li> <li>• Sensitivity: 99dB</li> <li>• Frequency Response: 43Hz-20KHz</li> <li>• Air Duct: Front</li> </ul>	4		
Set	<b>Input/Output XLR Cable Connector</b> <ul style="list-style-type: none"> <li>• Input/Output</li> <li>• 3P XLR Female + 3P XLR Male</li> <li>• XLR Connector</li> </ul>	50		
Set	<b>Wired Microphone</b> <ul style="list-style-type: none"> <li>• Sensitivity mvpa: 2.50</li> <li>• Height (mm) / (in): 173.8mm / 6.846 in</li> <li>• Width (mm) / (in): 52.6 mm / 2.071 in</li> <li>• Depth (mm) / (in): 52.6 mm / 2.071 in</li> <li>• Transducer Type: Dynamic</li> <li>• Polar Pattern: Cardioid</li> <li>• Sensitivity dBV/Pa: -52.00</li> <li>• Frequency Range To (kHz): 15</li> <li>• Impedance (Ω): 600</li> <li>• Frequency Range From (Hz): 50</li> <li>• Weight (g) / (lbs): 244g / 0.494 lbs</li> </ul>	4		
Set	<b>Microphone Stand</b> <ul style="list-style-type: none"> <li>• Material: Metal Base</li> <li>• Height Adjustment: Adjustable from 1080mm to 1750mm</li> </ul>	4		

	<ul style="list-style-type: none"> <li>• Base: Weighted base for stability</li> <li>• Type: Heavy Duty microphone stand</li> </ul>			
Set	<b>Wireless Microphone</b> <ul style="list-style-type: none"> <li>• Wireless Microphone (1 receiver 2 wireless microphone)</li> <li>• Type: UHF Wireless Microphone System</li> <li>• Frequency Range: 610-670 Mhz</li> <li>• Number of Channels: 200</li> <li>• Transmission Range: Up to 200 meters</li> <li>• Frequency Matching: Infrared (IR)</li> <li>• Pilot Mode: Pilot and digital ID</li> <li>• Microphone Body: Metal</li> <li>• True Diversity Dual UHF Microphone 200m</li> <li>• Receiver Power: 220V/50Hz</li> <li>• Tru Diversity: Yes</li> <li>• Total Harmonic Distortion: &lt;0.5%</li> </ul>	2		
Set	<b>XLR Cable (100M)</b> <ul style="list-style-type: none"> <li>• Ground with Cotton Shield</li> <li>• 3 Conductors</li> <li>• Double Shield</li> <li>• Microphone Cable</li> <li>• Audio Cable</li> <li>• Good Copper Screen</li> <li>• OD: 6.7mm (100M)</li> <li>• Microphone Cable</li> </ul>	5		
Set	<b>Portable Rechargeable Powered Speaker with Wireless Microphone</b> <ul style="list-style-type: none"> <li>• Sensitivity: 98dB</li> <li>• LF: 12" Woofer (2" Voice coil size)</li> <li>• HF: 1.5 Titanium Dome Tweeter</li> <li>• Freq. Resp.: 45Hz-20kHz</li> <li>• AC Input: 220V 50-60Hz</li> <li>• Amp. Power: 450W MAX</li> <li>• Impedance: 4 ohms</li> <li>• Input Gain: line: +20 dBu/ Mic: +40dB</li> <li>• Input Connector: Line (XLR, RCA &amp; PL), Mic (PL &amp; XLR)</li> </ul>	2		



	<ul style="list-style-type: none"> <li>• Dimension (HxWxD): 122(H) x 37(W) x 33(D)cm</li> <li>• System Type: 12" 2 Way Full Range</li> <li>• Signal indicator: Limit, Clip</li> <li>• Crossover Freq.: 3KHz</li> <li>• Output Connector: Line (XLR &amp; PL link out), Speaker (Speakon to passive speaker)</li> </ul>			
Set	<b>20K VA Automatic Voltage Regulator (AVR)</b> <ul style="list-style-type: none"> <li>• Capacity: 20,000 VA (20KVA)</li> <li>• Phase Type: Single Phase (AVR)</li> <li>• Voltage Input Range: 140V to 250V</li> <li>• Voltage Output: 220V</li> <li>• Voltage Stabilization Accuracy: 220V <math>\pm</math>3</li> <li>• Over-Voltage Protection Value: 246V <math>\pm</math>4V</li> <li>• Under-Voltage Indication Value: 186V <math>\pm</math>4V</li> <li>• Load Power Factor: 0.8</li> <li>• Adjusting Time: 1.5 seconds</li> <li>• Long Delay: 5 <math>\pm</math>2 minutes for startup safety.</li> <li>• Short Delay: 5 <math>\pm</math>2 seconds for quicker voltage response.</li> <li>• Insulation Resistance: 5 M<math>\Omega</math>.</li> <li>• Winding Material: 100% pure copper winding</li> <li>• True Output Power: 100% true output power</li> </ul>	1		
Set	<b>Audio Rack Cabinet</b> <ul style="list-style-type: none"> <li>• MC-14U</li> <li>• Procace with mixer on top with wheel</li> <li>• Original IMIX/Trident Procace</li> </ul>	1		
Set	<b>Power Distribution Unit (PDU)</b> <ul style="list-style-type: none"> <li>• Front 8-position switch</li> <li>• Sub-control Switch : Yes</li> <li>• Surge Protector : Yes</li> <li>• Back 8 16A-socket output</li> <li>• Overload Protection : Yes</li> <li>• Type: Extension Sock</li> <li>• With cover (front switch)</li> </ul>	1		

	<ul style="list-style-type: none"> <li>• Grounding: Standard Grounding</li> <li>• Voltage: 220-250V</li> </ul>			
	<b>Wire Speaker</b> <ul style="list-style-type: none"> <li>• Cable Size: 14 AWG</li> <li>• 2 x 2.5mm<sup>2</sup></li> <li>• Cable Color: Black</li> <li>• Cable Length: 100M</li> <li>• Professional Speaker Wire</li> </ul>	2		
<b>TOTAL AMOUNT</b>				

Total amount in words:

---

**The above-quoted prices are inclusive of all costs and applicable taxes.**

Very truly yours,

\_\_\_\_\_  
Name/ Signature of Representative

\_\_\_\_\_  
Name of Company

\_\_\_\_\_  
Contact No.

\_\_\_\_\_  
Email Address

Mayor's Permit No. \_\_\_\_\_

PhilGEPS Registration No. \_\_\_\_\_

(Please submit the photocopies of the above documents upon submission of quotation)



Gate 3, South Harbor, Port Area, Manila 1018

+63 (02) 8705-6000, +63 (02) 8527-1968 | www.customs.gov.ph | boc.cares@customs.gov.ph